



Tabela udźwignów Q i wysokości podnoszenia H

Udźwign Q[t] i wysokość podnoszenia H[m]

Wysięg [m]	Lm1		Lm2		Lm3		Lm4	
	Q [t]	H [m]	Q [t]	H [m]	Q [t]	H [m]	Q [t]	H [m]
3,0	20,0	8,820	-	-	-	-	-	-
4,0	15,6	8,180	12,0	14,950	6,2	21,223	-	-
5,0	12,0	7,307	9,5	14,460	6,0	20,932	3,0	27,554
6,0	9,4	6,164	7,6	13,996	5,3	20,588	2,6	27,270
7,0	7,0	4,157	6,1	13,329	4,6	20,191	2,2	26,930
7,5	6,0	1,257	5,5	13,037	4,35	19,898	2,0	26,732
8,0	-	-	5,0	12,571	4,0	19,742	1,9	26,460
9,0	-	-	4,0	11,728	3,5	19,066	1,65	25,755
10,0	-	-	3,2	10,617	3,0	18,502	1,45	25,533
11,0	-	-	2,6	9,396	2,55	17,891	1,25	24,662
12,0	-	-	2,1	7,679	2,1	17,006	1,1	24,184
13,0	-	-	1,7	5,070	1,8	16,292	1,0	23,934
13,5	-	-	1,5	1,275	1,6	15,793	0,95	23,934
14,0	-	-	-	-	1,4	15,276	0,9	22,445
15,0	-	-	-	-	1,2	13,912	0,82	22,393
16,0	-	-	-	-	0,9	12,751	0,75	22,072
17,0	-	-	-	-	0,75	10,918	0,7	21,609
18,0	-	-	-	-	0,5	8,960	-	-
19,0	-	-	-	-	0,45	5,539	-	-
19,5	-	-	-	-	0,4	1,275	-	-